

# SPECIFICATION




*Power Link the World*

## **MODEL R650B RG SERIES (FOR 50Hz DIESEL GENSET)**

Revision: B2 (02/23)

To inquire the latest revision of  
document, visit our website at:  
[www.powerlinkworld.com](http://www.powerlinkworld.com)



# RG series

## R650B

50 Hz @ 1500rpm.3-phase/4-wiring



### 1 Standards & Conditions

#### Design Standards

The designs and the productions are in conformity with:

- Conformance Européenne (CE)
- ISO8528-5:2005
- GB/T2820.5-2009

#### Environmental Operating Conditions

- Installation place: Outdoors or indoors (well ventilated).
- Ambient temperature: -25°C to 45°C. The coolant heater is needed when the temperature is below 5°C
- Humidity: Less than 90%.
- Altitude: Below one thousand (1000) meters above sea level.

#### Factory Inspection

- Inspection items.
- Protection devices working test.
- Starting ability in normal temperature.
- 50% rated power load moment capability.
- Voltage deviation and speed variation: 0%, 25%, 50%, 75%, 100%, 110% Load.

#### Painting Process

- Painting process specifications and colors are based on the manufacturer's standard.
- The customer could also choose the color which the manufacturer offers.


### 2 General Features

- Cummins engine 6M33G6D3/5
- Close coupled to Leroy Somer alternator LSA47.3L10
- Microprocessor controller PLC500
- ABB main circuit breaker: 1250A
- Rotate speed governor: ECU
- Excitation System: Self Excited,SHUNT
- A.V.R.Model: R250
- Key switch
- Emergency stop switch
- ATS (automatic transfer switch) receptacle
- Remote run connector

- 2x12V/120AH sealed for life maintenance free battery
- Lockable battery isolator switch
- Powder coated canopy
- 50°C radiator
- Steel base frame with forklifts
- Vibration isolators between the engine/alternator and base frame
- Dry type air filter
- Base fuel tank with 8 hours running
- Drain points for fuel tank
- Operator's Manual / Specifications

### 3 Equipment Specification


#### General technical data



Model..... R650B  
 Tank capacity..... 1100L  
 Dry weight.....7608kg  
 Sound pressure level @ 7m..... 73dBA  
 Dimensions L×W×H.....4982.5x1700x2456mm  
 Standby Power ..... 713kVA/570kW  
 Prime Power..... 650kVA/520kW


Voltage	380V	400V	415V	440V	
Ampere	967.6A	938.2A	904.3A	853.0A	
<b>Genset Fuel Consumption</b>					
Frequency/Load	25%	50%	75%	100%	110%
50Hz (L/h)	37.9	67.1	100	136.3	153.3

## Dck Yf GrghYa




Engine Manufacturer/Brand.....	Cummins
Engine Model.....	6M33G6D3/5
Dimensions L×W×H.....	2798 x 1600 x 1900mm
Dry Weight (approx.) .....	2090kg
Number of Cylinders.....	6
Bore.....	150mm
Stroke.....	185mm
Displacement.....	19.6L
Compression Ratio.....	15
Type of injection.....	Direct injection
Intake System.....	Turbocharged and Charge Air Cooled
Intake Resistance.....	≤5kPa
Cooling System.....	Water cooled
Fan.....	Pusher
Battery Voltage.....	24V
Type of Fuel.....	No.2 or ASTM D975
Type of Oil.....	API CD/SE or CCMCD4
Oil Capacity.....	64L
Type of Coolant.....	Glycol mixture
Coolant Capacity engine only.....	44L
Back Pressure.....	≤6.8kPa
Standby Power.....	633kW
Prime Power.....	575kW
Fuel Consumption(100%load).....	136.3L/h

## Alternator



Alternator Manufacturer/Brand.....	Leroy Somer
Alternator Model.....	LSA47.3L10
Exciter.....	Brushless
Cooling Fan.....	Cast alloy aluminum
Windings.....	100% copper
Insulation Class.....	H
Winding Pitch.....	2/3
Terminals.....	12
Drip Proof.....	IP23
Altitude.....	≤1000m
Overspeed.....	2250rpm
Air Flow.....	N/A
Voltage Regulation.....	±1.0%
Total Harmonic TGH / THCat no load < 1.5 % - on load < 5%	
Telephone Interference.....	THF<2%;TIF<50


## PLC500 Control System




PLC-500 is a microprocessor based control unit containing all necessary functions for protection of the genset and the breaker control. Furthermore, it contains all necessary three-phase measuring circuits and presents all values and alarms on the LCD display. The module has the function of load sharing which enables the module to share the active load (kW) equally when operating in parallel with other gensets. The load sharing is performed so each genset takes a portion of the load that is calculated in percent according to the nominal power.

- Microprocessor control, with high stability and credibility
- Monitoring and measuring operational parameters of the genset
- Indicating operation status, fault conditions, all parameters and alarms
- Multiple protections; multiple parameters display, like pressure, temp. etc.
- Manual, automatic and remote work mode selectable
- RS232 & RS485 can be used at the same time
- Real time clock for time and date display, overall runtime display, 250 log entries

## 4 Overall Dimensions



## 5 Control System



Ref.	Description
1	Charge indicator
2	Not ready
3	Control panel lamp
4	Control module
5	Timer
6	Emergency stop button
7	Key switch
8	Live wire terminals
9	Neutral wire terminal
10	Main circuit breaker

# **SPECIFICATION**

**RG SERIES DIESEL GENSET**

**R650B**

Revision: B2 (02/23)

To inquire the latest revision of  
document, visit our website at:  
[www.powerlinkworld.com](http://www.powerlinkworld.com)

