


MOBILE LIGHTING TOWER

MS2000





MS2000



Smart Control Panel



Easy Inspection and Maintenance




Customized Optional Mechanical and Electrical Configuration



Easy to Move



Space-Saving



Excellent Performance



180000~300000 lumen



4 x 500W metal LED lamps



Unfold size (mm): 2900 x 2100 x 9000



Tier 4 Final Emission Standard



9 Meters Height | Hydraulic Lifting



KUBOTA Z482 series engines are powerful and adaptable to a wide range of environments



Highly efficient LED lights, achieving 70% energy conservation



359° Rotated Pole | 0~90° Lamp Head



50°C radiator



50000 hours of overall overhaul



Applicable temperature from -40 to 45°C



MOBILE LIGHTING TOWER

MS2000

Configuration

Standard Configuration

- Kubota engine
- Permanent magnet generator
- Control module
- Governor type: Electronic control
- Nine metre masts with manual rotation 359°
- 4x500W LED lamps
- Emergency stop switch

- DC input socket for charging battery
- Lockable battery isolator switch
- Power coated canopy
- Dry type air cleaner
- Fuel tank
- Fuel drain outlet

Optional Configuration

- Spherical connector
- Leakage sensor
- Inclination sensor
- Negative switch (2P)
- Breaker Lock
- AC input socket
- AC socket output



POWERink
Energy Systems

Power Link the World

www.powerlinkenergy.com

If there is data changes without notice, please contact us or your local agents for more details.